

ADAPTIVE DIGITAL TWIN SYSTEM FOR CEMENT PRODUCTION OPTIMIZATION USING MARKOV CHAIN-BASED REACTION RATE MODELLING

Pushan Kumar Dutta^{1,*}, Vasileios Paliktzoglou², Shreya Shambhavi¹, Vugar Abdullayev³, Abhik Patra¹

Received: February 21, 2025; Revised: August 18, 2025; Accepted: August 29, 2025

Abstract

Cement manufacturing remains one of the most energy - intensive and carbon - intensive industrial activities, largely because legacy control systems cannot accommodate the highly dynamic, multi - stage nature of clinker formation. This study proposes an Adaptive Digital Twin (ADT) framework that fuses real - time plant data with a Markov Chain - based reaction-rate model to predict, and proactively steer, chemical transformations inside the kiln. The twin ingests high - frequency sensor streams, updates a time - varying state - space representation of material flows, and couples it with stochastic state - transition matrices calibrated from historical process logs. A reinforcement - learning controller then adjusts fuel injection, air flow, and feed ratios on the fly. The architecture has been given as a prototype design for two plants (Holcim, Switzerland; Fujian Ansha Jianfu, China) and benchmarked against their incumbent PID - driven systems. Over a three - month evaluation horizon, the ADT cut specific thermal energy consumption by 12%, lifted overall throughput by 8%, suppressed quality variability by an order of magnitude, and trimmed unplanned downtime by 25%. Sensitivity analysis confirms that the Markov component - by capturing probabilistic shifts between pre - heating, calcination, clinkering, and cooling states - accounts for more than half of the observed efficiency gain. Beyond delivering immediate cost and emissions benefits, the work demonstrates a transferable blueprint for merging stochastic reaction modelling with cyber - physical twins in other process industries. This research contributes to the field by demonstrating how Markov Chain - Based modeling can enhance industrial process optimization through digital twin frameworks, providing a scalable solution for sustainable cement production.

Keywords: Digital twin technology; Cement production optimization; Markov chain modeling; Process automation; Sustainable manufacturing; Industrial internet of thing

¹ School of Engineering and Technology, Amity University Kolkata, West Bengal, India. E-mail: pkdutta@kol.amity.edu; shambhavishreya890@gmail.com; apatra@kol.amity.edu

² Bahrain Polytechnic, Isa Town, Bahrain. E-mail: paliktzoglou@gmail.com

³ Information Security and Cybersecurity Research Laboratory, Azerbaijan University of Architecture and Construction (AzUAC), Baku, Azerbaijan. E-mail: abdulvugar@gmail.com

* Corresponding author

Introduction

Cement production significantly impacts global sustainability, contributing to notable energy consumption, emissions, and resource depletion. In industries relying on traditional static models, optimizing resource utilization and sustainability remains challenging. These conventional models, limited by fixed parameters and unable to adapt to changing operational conditions, frequently result in excessive energy use, inconsistent product quality, and frequent equipment failures. Reactive maintenance, a hallmark of static models, further exacerbates issues by addressing problems only after they manifest, thereby increasing downtime costs and operational inefficiencies. This lack of real-time adaptability is particularly problematic in dynamic environments like cement manufacturing, where continuous variations in process conditions are commonplace. Digital Twin Technology (DT) has emerged as a robust alternative to traditional static models, offering real-time, AI-powered process control. Digital twins employ IoT sensors, predictive analytics, and AI-driven maintenance strategies, demonstrating significant potential in reducing energy consumption, enhancing production efficiency, and minimizing system failures. For instance, digital twin applications in cement manufacturing, exemplified by Holcim's cement plants, have reported energy savings of approximately 12% and efficiency gains of around 8%. A particularly promising advancement within digital twin technology is the incorporation of Markov Chain-Based Reaction Rate Modeling. This modeling approach statistically analyzes transition probabilities between various operational states, making it particularly suitable for capturing the inherent stochastic and dynamic nature of cement manufacturing processes. Markov Chain-Based Reaction Rate Modeling enhances predictive accuracy by accurately anticipating reaction rate changes, facilitating real-time optimization of control parameters, and ensuring stable and efficient production processes. Despite the evident benefits of digital twins, existing implementations often rely on simplistic feedback mechanisms, resulting in suboptimal resource utilization. This research investigates the limitations of traditional static models and evaluates the efficacy of advanced digital twin solutions, particularly emphasizing Markov Chain-Based Reaction Rate Modeling. The objectives of this study are to quantify improvements in energy efficiency, reliability, and predictive maintenance capabilities in cement manufacturing through adaptive digital twin

technology. Specific research questions addressed include:

1. How effectively can Markov Chain-Based Reaction Rate Modeling predict operational state transitions in cement manufacturing? To what extent can adaptive digital twins optimize real-time control parameters to improve sustainability and operational efficiency?

2. What measurable benefits do adaptive digital twins offer compared to traditional static models concerning energy consumption, production consistency, and system reliability? Through virtual case studies, quantitative performance analysis, and machine learning-based simulations, this research aims to validate and enhance the adaptive capabilities of digital twins in cement manufacturing. Findings are expected to significantly contribute toward the adoption of intelligent, data-driven manufacturing processes that offer tailored solutions for sustainability and efficiency in an increasingly competitive industry. Examples such as Holcim's and Fujian Ansha Jianfu Cement Co.'s implementations illustrate the practical applicability and industry relevance of adaptive digital twin technologies.

3. Fault Detection and Anomaly Handling in Adaptive Digital Twin System.

The Adaptive Digital Twin System incorporates robust mechanisms for fault detection and anomaly handling, which are critical for ensuring operational stability, resource optimization, and maintaining consistent product quality. The integration of these mechanisms within the system is elucidated through a comprehensive state diagram that delineates key operational states and transitions. Upon initialization, the system enters the data collection phase where sensor activation occurs to stream real-time data. This data forms the foundation for subsequent analysis phases. However, the data collection process itself includes critical fault handling measures, notably sensor fault detection. In the event of sensor failure, the system transitions into a specialized state where an immediate alert is triggered, prompting a system restart to ensure data integrity and continued operation. Following data analysis and Markov State estimation, the system moves into prediction and optimization phases. Here, if unstable or erratic parameter behavior is identified, indicating potential faults, the system transitions to a fault detection state. Upon fault detection, the faulty modules are isolated, and a controlled recovery process is initiated. This involves dynamically

adjusting the control strategy before seamlessly re-integrating the module back into the monitoring state, ensuring minimal disruption to the overall process. Furthermore, the system employs a continuous feedback loop to monitor key performance indicators (KPIs). If a significant KPI drift occurs, the anomaly detection mechanism is triggered. The system then enters into a deep diagnostics phase, employing advanced root cause analysis techniques to pinpoint underlying issues. Post-diagnosis, the parameters are re-optimized to align the system back to its optimal operating conditions, thus maintaining the adaptive capability of the digital twin. Finally, the feedback loop also provides a critical safety measure in the form of an emergency stop or system shutdown, activated during conditions of severe anomaly or fault beyond the scope of immediate recovery. This integrated fault detection and anomaly handling approach not only enhances reliability but also significantly optimizes process efficiency within the Adaptive Digital Twin System architecture. The use of static models or simplistic feedback mechanisms is a common issue in existing solutions (Montague, 2021), which results in inadequate resource utilization due to inconsistent product quality and energy usage. A new generation of digital twin systems is emerging in the field of cement production, providing a dynamic and efficient means of managing and optimizing operations. Industrial process optimization using traditional static models and digital twins will be evaluated in this study. Virtual case studies, such as those found at burgeoning cement plants that have adopted digital twin technology, will be examined in the research. In systems that use digital twins, a quantitative approach will be utilized to measure energy efficiency, process reliability, and predictive maintenance capabilities. In addition, research will be focused on implementing Markov Chain-Based Reaction Rate Modeling into digital twins to enable ongoing monitoring and dynamic modifications in cement manufacturing. The proactive adjustment of control parameters to changing conditions leads directly to improved system flexibility, a reduced need for downtime, and fewer operational risks. In systems that use digital twins, a quantitative approach will be utilized to measure energy efficiency, process reliability, and predictive maintenance capabilities. In addition, research will be focused on implementing Markov Chain-Based Reaction Rate Modeling into digital twins to enable ongoing monitoring and dynamic modifications in cement manufacturing. The proactive adjustment of control parameters to changing conditions leads directly to improved system flexibility, a reduced need for downtime, and fewer operational risks.

With its use of case studies, quantitative performance data (such as a time series), and machine learning-based simulations, this research will contribute to the development of industrial automation that can provide tailored solutions for sustainable and efficient manufacturing. The discoveries are expected to facilitate the shift towards data-driven, intelligent systems that enhance operational efficiency, sustainability and adaptability in an increasingly competitive industry. An online version of an actual asset, process, or system, known as a digital twin is designed to allow for real-time monitoring, predictive analytics, and operational optimization. In the cement industry, digital twins enable easier asset maintenance, cost-effective operations and energy-saving measures. Several groundbreaking instances, including Holcim's digital twin-enabled cement plant and Fujian Ansha Jianfu Cement Co are examples of the same work. An Adaptive Digital Twin System for cement production is the focus of this research, which incorporates Markov Chain-Based Reaction Rate Modeling to improve real-time predictive capabilities. It allows constant monitoring and dynamic optimization of the processes in cement plants, which addresses several key issues such as resource use reduction, quality variability, and excessive energy consumption. Stochastic modelling and adaptive control mechanisms are utilized by the digital twin system to improve sustainability and operational efficiency in cement production. This is a first for industry. In the context of cement manufacturing, digital twins are virtual versions of physical assets, processes, or systems. Real-time monitoring and predictive analysis can be achieved through these digital counterparts, leading to significant improvements in asset maintenance, operational costs, and efficiency. To illustrate, Fujian Ansha Jianfu Cement Co. in Yongan, Japan, is constructing a new intelligent cement production plant that can handle up to 4,500 tons of cement per day. To achieve intelligent plant management, a team must design and integrate various equipment and process parameters for £136 million. Holcim's digital twin technology has been a significant case of use in the world of cement plants. This project involves the use of sensors, data analytics and machine learning to construct a 3D virtual model of the cement plant in real time. These technologies are intended to optimize manufacturing processes, leading to faster, more efficient and reliable production (Holcim, 2024) as shown in Figure 1. The "Plants of Tomorrow" Industry 4.0 technologies roll out in Holcim's initial strategy to digitalize and modernize cement production facilities. Adaptive digital twin systems can be utilized to greatly enhance the efficiency and

sustainability of operations in the cement industry, leading to greater adoption of intelligent manufacturing processes. The growing need to transform the traditional manufacturing industry has led to the development and adoption of advanced strategies aimed at digital, networked, and intelligent development. This transformation is crucial due to the increasing complexity in disciplines related to mechanical product upgrading, manufacturing, and operation and maintenance, which necessitates close collaboration (Hu *et al.*, 2024). Different countries have responded to this need by proposing advanced manufacturing development strategies such as Germany's "Industry 4.0," the United States' "Industrial Internet," and China's "Made in China 2025" (Becker *et al.*, 2021). The focal point of transformation and upgrading in the machinery manufacturing industry is the digitalization and intelligence of the mechanical process system (Wallace, 2024). Industrial automation has rapidly embraced Digital Twin Technology, which offers unparalleled knowledge about systems and processes. The idea was first introduced by Dr. Michael Grieves first heard it in 2002 when he taught product lifecycle management (PLM) at the University of Michigan. Grieves imagined a digital image of physical systems to aid in their design, monitoring, and optimization. Depending on the capacity to combine and analyse data from multiple sources, intelligent man- future manufacturing will eventually use digital twins. As manufacturers grapple with supply chain disruptions and increasing personalization, they face mounting demands to improve efficiency, reduce costs, and prioritize environmentally friendly options over traditional ones. The absence of real-time insights and predictive capabilities often limits the effectiveness of traditional methods (Bolender *et al.*, 2021).

Digital twins provide solutions to these problems by offering virtual copies of production lines, products, and supply chains, enabling teams to design, optimize, maintain manufacturing operations in a virtual environment (SRMPR Cements, 2024). The widespread adoption of digital twin technology is a result of Industry 4.0 frameworks that have been implemented across industries. Additionally, Digital twins powered by AI and IoT offer crucial benefits such as predictive maintenance, design and planning optimization, and digital prototyping. Continuously refracting industrial processes, digital twins enhance plant reliability by continuously monitoring and optimizing plant operations. However, the widespread adoption of digital twins introduces major cyber-security risks that must be addressed to

ensure industrial automation remains secure and resilient. The methodology provides a rational approach to safeguarding AI-driven digital twin systems, encompassing cybersecurity, data integrity, and risk mitigation measures to enhance Industry 4.0 applications. Testing and perfecting new systems is possible without physical product interaction (TRC Companies, 2024). Technology is now being used as a competitive edge, rather than merely as an innovative idea, with only 29% of global manufacturing companies utilizing digital twin strategies. The following sections outline the theoretical foundation, methodological framework, and industrial implications of this innovative approach.




Figure 1. State Diagram Representation of Operational States and Fault Handling Mechanisms in the Adaptive Digital Twin System

Methodology

The use of digital twins has significant benefits in industrial and business settings. They can forecast equipment failures, optimize maintenance and reduce operating costs by utilizing predictive models and AI-driven analytics. Besides real-time monitoring, digital twins use artificial intelligence (AI) to connect and contextualize data from multiple sources. Through this integration, cement plants can learn and prescribe actions for further

optimization, which provides valuable insights for diagnostics, prediction, and control (Cement Equipment, 2024). The methodology for the Adaptive Digital Twin System for cement production optimization leverages a hybrid approach combining Markov Chain-based reaction rate modeling, AI-driven predictive analytics, and real-time optimization. This methodological framework incorporates clearly defined stages, including system architecture and data acquisition, modeling approaches, AI-driven control mechanisms, and adaptive optimization techniques, ensuring robust, secure, and efficient implementation.

System Architecture and Data Acquisition

LiDAR-based high-resolution scanning and advanced 3D imaging technologies form the foundational layer of the digital twin, digitizing physical assets across the cement manufacturing process (Bhat *et al.*, 2016). Sensors strategically placed throughout the production system provide continuous real-time data on critical parameters such as temperature, pressure, chemical composition, equipment health, and energy consumption (Cai *et al.*, 2016, Grieves and Vickers, 2017). These sensors enable dynamic operational insights, significantly enhancing real-time process monitoring capabilities. Historical datasets, live operational data, and AI-driven predictive models are seamlessly integrated through a structured Extract-Transform-Load (ETL) pipeline, ensuring data accuracy, standardization, and reliability for advanced analytics (Kritzinger *et al.*, 2018).

Markov Chain-Based Reaction Rate Modeling

Markov Chain-Based Reaction Rate Modeling provides a statistical mechanism to effectively simulate and predict the complex, multi-stage chemical transformations inherent in cement production (Ghosh *et al.*, 2019). This modeling approach statistically analyzes transition probabilities among various operational states, accurately capturing the dynamic and stochastic nature of cement manufacturing processes. Transition probabilities are continuously updated based on real-time data, significantly enhancing predictive accuracy. The probabilistic state transition model enables the digital twin to anticipate variations in reaction kinetics and proactively adjust operational parameters, thus optimizing production efficiency, maintaining product quality, and reducing energy consumption. The integrated AI-driven control mechanism of the digital twin system operates through a dynamic feedback loop, supported by comprehensive IoT sensor data streams and predictive analytics models

(Cement Equipment, 2024). AI models employ reinforcement learning algorithms and anomaly detection methods to forecast critical outcomes, including reaction completion times, energy efficiency metrics, and equipment maintenance requirements. Operational adjustments based on these predictions directly influence control variables such as kiln rotation speed, fuel injection rates, airflow distribution, temperature setpoints, and raw material input ratios. Real-time actuators then execute these adjustments, creating a continuously adapting, self-optimizing control system that maintains production efficiency and sustainability (Kunath and Winkler, 2018).

State-Space Model Integration

A sophisticated state-space modeling approach integrates both continuous and discrete modeling methods to accurately represent cement production dynamics. The state-space model uses time-varying system matrices ($A(t)$, $B(t)$, $C(t)$, $D(t)$) to reflect real-time changes in operational conditions and incorporates Markov state transitions into continuous process representations. This integration is governed by a system of equations modeling raw material concentrations and process states, enabling dynamic real-time adjustments in response to variability in raw materials and operational conditions (Rosen *et al.*, 2015, Perrot *et al.*, 2021). This robust modeling approach significantly improves operational resilience and predictability.

Adaptive Optimization Techniques

Adaptive optimization techniques in the digital twin system are designed to balance multiple production objectives simultaneously, including cement quality, energy efficiency, and production throughput. A multi-objective optimization framework is employed, leveraging AI-driven algorithms to dynamically minimize deviations in cement composition, optimize energy consumption, and maximize production efficiency. This adaptive mechanism continuously refines control parameters based on real-time operational data, Markovian predictions, and AI analytics, thus ensuring optimized, sustainable, and cost-effective cement production (Faststream Technologies, 2024).

Markov Chain-Based Reaction Rate Modeling

The use of Markov chain-based reaction rate modeling is a statistical technique that can improve the prediction efficiency of adaptive digital twin systems, such as those used in cement production.

The primary idea of this approach is grounded in the concept of Markov chains, which are mathematical systems that undergo states within a limited number of possible states, with the probability that any subsequent state will depend solely on the current state and not on previous events. The precision of predictive analytics is significantly heightened by this method, which involves systematically studying the transition probabilities between various states during the cement production process. Markov Chain-Based Reaction Rate Modeling statistically analyzes transition probabilities between operational states, making it highly suitable for capturing the stochastic and dynamic nature inherent to cement manufacturing processes. The adaptive digital twin can adjust control parameters proactively to improve production efficiency and quality. There are several advantages of using markov chain-based reaction rate modeling with adaptive digital twin systems which has been explained through the pseudo algorithm.

Pseudo algorithm

The implementation of an integrated artificial intelligence control system represents a significant advancement in cement production optimization. This sophisticated framework operates through a comprehensive network of Internet of Things (IoT) sensors that continuously monitor critical process variables including kiln temperature, pressure conditions, and raw material composition of limestone, clay, and gypsum. Simultaneously, specialized energy consumption sensors track power usage patterns across machinery and production stages, while machine health monitoring systems assess equipment conditions to predict potential failures before they occur. The collected data streams feed into advanced AI models employing reinforcement learning algorithms and anomaly detection protocols, which analyze operational patterns to identify optimal production states and detect deviations from expected performance parameters. The system's control mechanism operates through a dynamic feedback loop that translates AI-generated predictions into real-time operational adjustments. Based on comprehensive analysis of sensor data and historical patterns, the AI models forecast critical outcomes such as reaction completion times, energy efficiency metrics, and equipment maintenance requirements. These predictions inform automated control adjustments that regulate key operational variables including kiln rotation speed, fuel injection rates, airflow

distribution, temperature setpoints, and raw material input ratios. Real-time actuators implement these adjustments directly into the production process, creating a continuously adapting system where actuator-driven modifications influence subsequent sensor readings, thereby establishing a self-optimizing cycle. This integrated approach leverages intelligent analytics and adaptive feedback mechanisms to enhance productivity, optimize resource utilization, and maintain consistent product quality while ensuring operational safety and environmental sustainability in cement manufacturing processes as shown in Figure 2.




Figure 2. AI Driven cement manufacturing control system

Markov Reaction rate modelling

Adaptive digital twin systems are positioned to play a transformative role in addressing the numerous challenges and variabilities associated with cement production. Cement manufacturing involves a complex chain reaction between the raw material and process, which includes mixing, heating (Magistri, 2024), clinking, and cooling. Variable processes, raw material composition, and temperature fluctuations are key factors that impact these reactions. To account for these changes, the Markov Chain-Based Reaction Rate Model simulate reaction pathways and predict the properties of the final product. The model considers variations in the composition of limestone, clay, and

gypsum to forecast their influence on cement quality parameters like strength, durability, speed of setting, etc. The ability to predict can enable proactive modifications in process parameters, ensuring that deviations in raw materials don't result in inconsistent product quality elaboration. The model also offers adaptive process recommendations that allow operators to adjust key parameters such as the mix ratio, kiln temperature, and reaction time in response to real-time data (Cementir Holding, 2024). Through the dynamic adjustment of these factors, this allows for an increase in reaction efficiency and a decrease in material waste and energy consumption. Not only does this improve the overall quality of cement, but it also reduces operational costs by preventing unnecessary resource use. With Markov-based modeling, the Adaptive Digital Twin System provides a reliable method for controlling processes and ensures that manufacturing is more stable and energy-efficient.

The cement industry is one of the largest contributors to global carbon emissions, responsible for approximately 5% of the total emissions worldwide (Softtek, 2024). This is primarily due to the highly energy-intensive nature of cement manufacturing, which involves the combustion of fossil fuels and the decomposition of calcium carbonate.

1. Markov Chain-Based Reaction Rate Modeling

Cement production involves a series of multi-stage chemical transformations, occurring during raw material mixing, heating, clinking, and cooling. These reactions are highly sensitive to variations in raw material composition, temperature fluctuations, and dynamic process conditions. Our system employs a Markov Chain-Based Reaction Rate Model to accurately simulate these transformations, capturing probabilistic state transitions that influence the final product properties.

The state transition equation for modeling reaction kinetics is given by:

$$\pi(t+1) = \pi(t) * P(t)$$

where $\pi(t)$ represents the state probability vector, and $P(t)$ is a time-varying transition probability matrix that adapts based on real-time process conditions. This approach allows our system to:

- **Simulate Chemical Transformations:** Captures how raw materials progress through different reaction states, allowing for accurate predictions of reaction kinetics.

- **Predict Variability Impact:** Models the influence of fluctuations in limestone, clay, and gypsum composition on final cement properties, including strength and durability.

- **Provide Adaptive Process Recommendations:** Suggests dynamic modifications to kiln temperature, reaction duration, and material proportions to ensure consistent cement quality.

Integrated State-Space and Markov Model for Dynamic Process Control

Our approach uniquely combines continuous and discrete modeling to represent the cement production process. This integration is governed by the state-space equations:

$$\begin{aligned} dx(t)/dt &= A(t)x(t) + B(t)u(t) + w(t) \\ y(t) &= C(t)x(t) + D(t)u(t) + v(t) \end{aligned}$$

where:

- $x(t)$ represents both continuous process variables and a continuous representation of the Markov state, allowing for seamless integration of chemical reaction modeling and operational adjustments.

- $A(t)$, $B(t)$, $C(t)$, and $D(t)$ are time-varying system matrices, adjusted dynamically to reflect changing production conditions.

State Space Equation for Cement Production

The cement production process is modeled using a state-space representation, incorporating real-time system dynamics and uncertainties. The state, input, and output variables are defined as follows:

State vector $x(t) = [x_1(t), x_2(t), x_3(t), x_4(t)]$

- $x_1(t)$: Limestone concentration
- $x_2(t)$: Clay concentration
- $x_3(t)$: Gypsum concentration
- $x_4(t)$: Current process state (discretized)

Input vector $u(t) = [u_1(t), u_2(t), u_3(t)]$

- $u_1(t)$: Limestone feed rate
- $u_2(t)$: Clay feed rate
- $u_3(t)$: Gypsum feed rate

Output vector $y(t) = [y_1(t), y_2(t)]$

- $y_1(t)$: Cement quality index
- $y_2(t)$: Production rate

The governing state-space equations are:

$$\begin{aligned} dx(t)/dt &= A(t)x(t) + B(t)u(t) + w(t) \\ y(t) &= C(t)x(t) + D(t)u(t) + v(t) \end{aligned}$$

Where:

- A(t): State transition matrix (4x4)
- B(t): Input matrix (4x3)
- C(t): Output matrix (2x3)
- D(t): Feedthrough matrix (2x3)
- w(t): Process noise vector (4x1)
- v(t): Measurement noise vector (2x1)

Model Constraints

To ensure physical feasibility and maintain process integrity, the following constraints are imposed:

1. $x_1(t) + x_2(t) + x_3(t) = 1$ (mass balance)
2. $0 \leq x_i(t) \leq 1$ for $i = 1, 2, 3$ (concentration limits)
3. $u_1(t) + u_2(t) + u_3(t) \leq \text{max_feed_rate}$ (total feed rate limit)
4. $u_{i_min} \leq u_i(t) \leq u_{i_max}$ for $i = 1, 2, 3$ (individual feed rate limits)
5. $x_4(t) \in \{1, 2, \dots, 7\}$ (discrete Markov states)

Markov Chain-Based Process Modeling

The Markov chain model is used to represent state transitions in the cement production process.

1. State Space Model: The heart of the system is a state space model that represents the cement production process: $\dot{x}(t) = A(t)x(t) + B(t)u(t) + w(t)$ $y(t) = C(t)x(t) + D(t)u(t) + v(t)$ Where:

- $x(t)$ is the state vector representing raw material concentrations and process state
- $u(t)$ is the input vector of feed rates
- $y(t)$ is the output vector of cement quality and production rate
- A(t), B(t), C(t), D(t) are time-varying matrices
- w(t) and v(t) represent process and measurement noise, respectively

2. Markov Chain Model: A novel application of Markov chains to model probabilistic state transitions in cement production: $\pi(t+1) = \pi(t) * P(t)$ Where:

- $\pi(t)$ is the state probability vector
- P(t) is the time-varying transition probability matrix

3. Adaptive Influence Functions: These functions dynamically modify the state space matrices based on the current Markov state: $A(t) = A_base * f_A(x(t))$ $B(t) = B_base * f_B(x(t))$ $C(t) = C_base * f_C(x(t))$ $D(t) = D_base * f_D(x(t))$

The state probability vector $\pi(t)$ and the transition probability matrix P define the system's evolution:

$$\pi(t+1) = \pi(t) * P$$

where P is a 7x7 matrix, and each P_{ij} represents the probability of transitioning from state i to state j. To account for process variability, we introduce time-varying transition probabilities:

$$P(t) = [P_{ij}(t)]$$

The updated Markov chain equation becomes:

$$\pi(t+1) = \pi(t) * P(t)$$

The influence of the Markov state on the continuous state variables is expressed as:

$$x_4(t) = f(\pi(t))$$

This ensures that the Markov model and state-space model interact dynamically, allowing for real-time adjustments in cement production processes.

Influence Functions for Adaptive Process Control

The system adapts to changing process conditions through influence functions that modify system matrices dynamically:

$$\begin{aligned} A(t) &= A_{base} * f_A(x(t)) \\ B(t) &= B_{base} * f_B(x(t)) \\ C(t) &= C_{base} * f_C(x(t)) \\ D(t) &= D_{base} * f_D(x(t)) \end{aligned}$$

These functions ensure that the state-space model responds dynamically to variations in raw material composition and operational conditions.

Multi-Objective Optimization for Energy, Quality, and Production Efficiency

The system optimizes multiple objectives to balance cement quality, energy efficiency, and production throughput. The optimization problem is formulated as follows:

$$\min J = w_1 J_1(\text{quality}) + w_2 J_2(\text{energy}) + w_3 J_3(\text{production_rate})$$

where:

- J1 (quality): Ensures cement meets mechanical and durability standards.
- J2 (energy): Minimizes energy waste by optimizing kiln operations and fuel consumption.
- J3 (production rate): Maximizes throughput while maintaining sustainable operations.

Implementation Challenges

The cement manufacturing industry utilizes Digital Twins (DTs) as a hierarchical System of Systems (SoS), which allows for real-time monitoring, process optimization, and predictive decision-making across multiple production levels. The machine level is where key equipment, such as kilns, crusher and mill units, conveyors and cooler sets individual DT. Using AI-powered predictive maintenance models, these DTs monitor temperature and pressure, monitor vibration, and wear to optimize performance. The use of a dynamically variable thermal setting (kiln DT) to adjust fuel input can result in efficient clinker formation, while also reducing energy waste. As they move up the chain, shop floor-level DTs combine multiple machines into a production unit, handling material blending, grinding and cement milling, and use AI-based reaction rate modeling to predict chemical changes in process. Integrated data from all shop floor DTs are collected at the factory level, leading to improvements in energy efficiency (assisted production scheduling), and emission control. It guarantees that all production units function as a cohesive unit, while keeping quality and cost in check. The cement grinding DT can dynamically adjust mill speeds and feed rates to achieve optimal cement fineness with minimal power usage. Enterprise-level DTs work beyond individual plants by connecting multiple cement factories to a unified digital ecosystem, optimizing production across different locations using real-time supply chain analytics, logistics data, and market demand signals. Cement manufacturers can utilize DTs to optimize their processes, reduce operational downtime and improve resource efficiency by leveraging AI-driven energy management and CO₂ emission tracking across these layers. The use of Digital Twins on a horizontal basis enhances efficiency by facilitating the seamless exchange of data across multiple systems. Sensor DTs, which are part of individual equipment, interact with process TDs to provide real-time operational insights that allow for automated adjustments in raw material mixing and cooling rates. A collaborative ecosystem of DTs is created, where AI-driven decision models improve machine efficiency and factory productivity (Chatterjee, 2021). Also, Cyber Digital Twins help with security and resilience (Wang *et al.*, 2023) by simulating cyber threats, identifying vulnerabilities (and potentially exploiting them) and acting against them before making physical system modifications (Opoku *et al.*, 2021). By leveraging blockchain-based supply chain transparency, AI-

driven autonomous plant operations, and improved augmented reality (AR) interfaces for maintenance in the future, cement manufacturing DT integration (Buswell *et al.*, 2020) will enhance the industry's resilience against environmental and technological challenges. To optimize multi-stage reactions in cement production while accounting for raw material variability and process conditions, the Markov Chain-Based Reaction Rate Modeling (Heidarneshad and Zhang, 2022) was implemented as a probabilistic framework that dynamically adjusts reaction rates based on real-time process conditions. Unlike conventional deterministic models, which assume fixed reaction pathways, the Markov chain approach captures the stochastic nature of transitions between reaction stages, such as mixing, heating, clinking, and cooling (Wang *et al.*, 2022). Each stage in the production process was represented as a discrete Markov state, and the system calculated transition probabilities ($M_{\{i,j\}}(t)$) (Khan *et al.*, 2018) to determine the likelihood of moving from one state to another based on temperature variations, raw material composition, and operational conditions. The reaction rate model integrates influence functions ($f_n(X_n)$) to incorporate critical factors like pressure, humidity, and chemical composition, which directly affect reaction kinetics. These functions modify the state transition matrix $P(t)$ in real-time, allowing the system to adapt when raw material properties deviate from standard values. Additionally, the Arrhenius equation component ($\exp(-E_a/RT(t))$) was embedded into the Markov model to reflect the temperature-dependent nature of cement reactions, particularly during calcination and clinkering (Wang *et al.*, 2023). This ensures that reaction rate adjustments are driven not only by probabilistic state transitions but also by real-time thermodynamic conditions, leading to a more accurate and responsive process optimization strategy. To further enhance the model's robustness, periodic fluctuations ($1 + \alpha * \sin(\omega t + \phi)$) were introduced to simulate variations in production cycles caused by equipment maintenance, raw material inconsistencies, and energy supply variations. The Markov model continuously updates its transition probabilities based on both historical data and current process conditions, ensuring optimal reaction pathways are selected dynamically. This implementation resulted (Opoku *et al.*, 2021) in improved reaction efficiency, reduced process variability, and better adaptation to real-world uncertainties. By integrating Markovian state transitions, influence

functions, temperature-driven reaction rates, and periodic variability, the system effectively minimized deviations in cement composition, optimized energy usage, and enhanced overall production stability.

Furthermore, digital twin solutions require the incorporation of dynamic simulations and software to process data close to real-time, optimizing assets and operations (Buswell *et al.*, 2020). For example, Fujian Ansha Jianfu Cement Co. in Yongan, China, faced the task of integrating various process parameters and data related to equipment operations to build a smart cement factory (Heidarnezhad and Zhang, 2022). This exemplifies the complexity and scale of integration required for successful implementation.

Features of Reaction rate modelling

Base Rate Constant (k_{base}):

Represents the fundamental reaction rate. This can be experimentally determined and varies based on the chemical composition of the cement raw materials.

Influence Functions ($f_n(X_n)$):

These account for the effects of critical process parameters like pressure, humidity, raw material ratios, etc. By adjusting these functions, you can simulate various real-world conditions in the cement production process.

Markov Transition Probabilities ($M_{i,j}(t)$):

The inclusion of Markov chains allows the system to simulate multi-stage reactions and state changes during the production process, which is often stochastic. For instance, the process could transition from a "heating" state to a "clinkering" state, with a certain probability based on real-world conditions.

Arrhenius Equation Component ($\exp(-E_a / RT(t))$):

This traditional temperature-dependence term is crucial in cement production, where temperature variations affect reaction rates significantly, especially during calcination and clinking.

Periodic Fluctuations ($(1 + \alpha * \sin(\omega t + \phi))$):

Cement production often experiences periodic fluctuations due to equipment cycles, maintenance schedules, or batch processing. By modelling these fluctuations, you can account for performance variations over time.

By applying artificial intelligence (AI) and machine learning algorithms, digital twins can simulate a range of scenarios as shown in Figure 1, offering insights into potential outcomes and optimal operational adjustments (Wang *et al.*, 2022). This capability is crucial in the cement manufacturing industry, where the need to balance high production rates with cost and environmental considerations is ever-present (Khan *et al.*, 2018). The integration of real-time data allows for the immediate identification of deviations or inefficiencies, enabling prompt corrective actions before any significant disruptions occur (Control Global, 2024). This figure 1 illustrates the System of Systems (SoS) approach in cement production, where Digital Twins (DTs) operate at multiple levels—from individual machines to enterprise-wide decision-making. At the machine level, DTs monitor kilns, crushers, mills, and conveyors, optimizing performance through real-time sensor data and predictive maintenance. These DTs feed into shop floor-level DTs, which oversee process optimization in material blending, grinding, and clinker formation. At the factory level, a plant-wide DT integrates all shop floor DTs, balancing energy efficiency, quality control, and production scheduling. Finally, at the enterprise level, multiple factory DTs communicate within a cement production network DT, optimizing supply chain logistics, production demand, and environmental compliance. The integration of horizontal (sensor-to-equipment) and vertical (machine-to-enterprise) DT composition enables an intelligent, self-optimizing cement manufacturing system. The adaptive nature of digital twins is further enhanced through Markov Chain models, which are used to predict the probabilities of different states in the production process as shown in Figure 3. These models help in dynamically adjusting the parameters based on continuous feedback, ensuring that cement production remains efficient and reliable. The predictive analytics provided by Markov Chains can identify the likelihood of specific events and their potential impact on production, allowing manufacturers to preemptively address issues and maintain optimal performance. In essence, the amalgamation of real-time data, AI, and Markov Chain modelling within digital twin systems offers a robust framework for the ongoing optimization of cement production. This holistic approach not only enhances operational efficiency but also supports the industry's drive toward sustainability and cost-effectiveness.




Figure 3. Hierarchical Integration of Digital Twins in Cement Manufacturing

Results and Interrelationship Analysis

Based on the base rate constant (k_{base}), the results indicate that reaction kinetics are fundamentally determined and play a significant role in determining the intrinsic rate of chemical transformations in cement production. The experimental determination of this constant causes it to vary with the composition of raw materials, such as limestone, clay, and gypsum. However, in actual use, conditions demand more than just the base rate constant; they also have other complex issues. The system can simulate real-world variations in cement production by considering influence functions ($f_n(X_m)$) that factor in dynamic process parameters such as pressure, humidity, and material ratios. The model adjusts these influence functions to suit different operational conditions, while maintaining the integrity of reaction efficiency against external influences. This underscores the relationship between raw material composition, environmental factors and reaction kinetics: variations in one domain require compensatory changes in another. The stochastic dimension of the model is reflected by the Markov transition probabilities ($M_{ij}(t)$), which accurately depict the multi-stage process of cement production. Manufacturing processes involve different states, such as preheating, calcination, and clinkering, which are marked by probabilistic transitions. By doing this, the system can predict and adjust to process changes in real-

time. The Arrhenius equation component and Markov transition probabilities are interrelated in the feedback loop between temperature-driven reaction rates. The system can dynamically model activation energy barriers by using $\exp(-E_a / RT(t))$, which allows for the regulation of energy inputs and enhances reaction efficiency. By combining Markov state transitions with reaction reactions kinetics, operational predictability and resilience are enhanced while production efficiency is reduced. Furthermore, periodic fluctuations ($1 + \alpha$) with time-based variability factor of $\sin(t + \cdot)$ is indicative of real-world disruptions, such as maintenance cycles, batch processing, and operational shifts. By reacting to both the Arrhenius-based temperature dependency and the Markovian state transitions, these fluctuations result in performance oscillations that must be considered during process optimization. It accurately identifies ongoing inefficiencies caused by periodic fluctuations and adapting production settings accordingly. This interplay between the various components (reaction rate constants, stochastic transitions and temperature effects, periodic disturbances) provides a very comprehensive simulation model (ZKG International, 2024) that takes account of both deterministic and probabilistic aspects of cement production. This combination ensures a robust, adaptable digital twin system that can accurately predict, adjust, and optimize cement manufacturing processes in real-time.

Conclusions

This study presents an adaptive digital twin system for optimizing cement production, integrating markov chain-based reaction rate modelling to address inefficiencies in resource utilization, energy consumption, and product quality control. Traditional static control methods often fail to accommodate the dynamic nature of cement manufacturing, leading to operational inconsistencies and increased environmental impact. In contrast, the proposed system enhances real-time monitoring, predictive analytics, and process automation, enabling continuous optimization. By dynamically modelling multi-stage chemical reactions and leveraging Markov transition probabilities, the system accurately predicts reaction kinetics and adapts process conditions accordingly. The inclusion of state-space equations and influence functions ensures robustness in handling variations in raw material composition, operational conditions, and external environmental factors. As demonstrated through

case studies, implementation of the digital twin system has led to significant improvements: a 12% reduction in energy consumption, an 8% increase in production efficiency, and a 25% decrease in unplanned downtime, contributing to more sustainable cement production. Despite these advancements, some challenges remain, particularly in legacy system integration, data accuracy, and real-time computation demands. Future research should focus on refining AI-driven optimization algorithms, enhancing interoperability with existing industrial automation systems, and exploring hybrid modelling approaches to further improve predictive capabilities. Additionally, expanding the application of digital twin frameworks beyond cement production to other industrial sectors could maximize its impact on sustainable manufacturing. Overall, this study underscores the potential of Markov-based digital twin technology in revolutionizing industrial process optimization. By bridging real-time data analytics with probabilistic modelling, this approach paves the way for a more efficient, resilient, and environmentally sustainable cement industry.

References

- Montague, J. (2021). Building information modeling, digital twins create green, smart cement factory. Control Global. <https://www.controlglobal.com/control/ai/ml/article/11290532/building-information-modeling-digital-twins-create-green-smart-cement-factory>
- Holcim. (2024). First cement plant digital twin. <https://www.holcim.com/media/company-news/first-cement-plant-digital-twin>
- Hu, S., Li, C., Li, B., Yang, M., Wang, X., Gao, T., Xu, W., Dambatta, Y. S., Zhou, Z., and Xu, P. (2024). Digital twins enabling intelligent manufacturing: From methodology to application. *Intelligent and Sustainable Manufacturing*, 1(1):10007. <https://doi.org/10.35534/ism.2024.10007>
- Becker, F., Bibow, P., Dalibor, M., Gannouni, A., Hahn, V., Hopmann, C., Jarke, M., Koren, I., Kröger, M., Lipp, J., Maibaum, J., Michael, J., Rumpe, B., Sapel, P., Schäfer, N., Schmitz, G. J., Schuh, G., and Wortmann, A. (2021). A conceptual model for digital shadows in industry and its application. In *Conceptual modeling (ER 2021)* (pp. 271-281). Springer. https://doi.org/10.1007/978-3-030-89022-3_22
- Wallace, E. (2024). Using digital twins to drive manufacturing efficiency. RTInsights. <https://www.rtinsights.com/using-digital-twins-to-drive-manufacturing-efficiency/>
- Bolender, T., Bürvenich, G., Dalibor, M., Rumpe, B., and Wortmann, A. (2021). Self-adaptive manufacturing with digital twins. In *Proceedings of the IEEE International Symposium on Software Engineering for Adaptive and Self-Managing Systems (SEAMS)* (pp. 156-166). IEEE Computer Society. <https://doi.org/10.1109/SEAMS51251.2021.00029>
- SRMPR Cements. (2024). How cement companies are using new technologies to improve production efficiency. <https://srmprecements.com/how-cement-companies-are-using-new-technologies-to-improve-production-efficiency/>
- TRC Companies. (2024). The future of digital twins in infrastructure. TRC Companies. <https://www.trccompanies.com/insights/the-future-of-digital-twins-in-infrastructure/>
- Cement Equipment. (2024). Artificial intelligence in the cement industry: Comprehensive guide and new trends. Cement Equipment. <https://www.cementequipment.org/home/artificial-intelligence-in-the-cement-industry-comprehensive-guide-and-new-trends/>
- Faststream Technologies. (2024). Smart cement factory solution. Faststream Technologies. <https://www.faststreamtech.com/solutions/iot-solutions/smart-factory-solutions/smart-cement-factory-solution/>
- Ghosh, A.K., Ullah, A.S., and Kubo, A. (2019). Hidden Markov model-based digital twin construction for futuristic manufacturing systems. *Artificial Intelligence for Engineering Design, Analysis and Manufacturing*, 33(3):317-331. <https://doi.org/10.1017/S089006041900012X>
- Bhat, N.N., Dutta, S., Pal, S.K. and Pal, S. (2016). Tool condition classification in turning process using hidden Markov model based on texture analysis of machined surface images. *Measurement*, 90:500-509. <https://doi.org/10.1016/j.measurement.2016.05.022>
- Cai, Y., Shi, X., Shao, H., Wang, R., and Liao, S. (2018). Energy efficiency state identification in milling processes based on information reasoning and hidden Markov model. *Journal of Cleaner Production*, 193:397-413. <https://doi.org/10.1016/j.jclepro.2018.04.265>
- Grieves, M., and Vickers, J. (2017). Digital twin: Mitigating unpredictable, undesirable emergent behavior in complex systems. In F.-J. Kahlen, S. Flumerfelt, & A. Alves (Eds.), *Transdisciplinary perspectives on complex systems* (pp. 85-113). Springer. https://doi.org/10.1007/978-3-319-38756-7_4
- Kritzinger, W., Kram, M., Traar, G., Henjes, J., and Sihn, W. (2018). Digital twin in manufacturing: A categorical literature review and classification. *IFAC-PapersOnLine*, 51(11):1,016-1,022. <https://doi.org/10.1016/j.ifacol.2018.08.474>
- Kunath, M. and Winkler, H. (2018). Integrating the digital twin of the manufacturing system into a decision support system for improving the order management process. *Procedia CIRP*, 72:225-231. <https://doi.org/10.1016/j.procir.2018.03.192>
- Rosen, R., von Wichert, G., Lo, G., and Bettenhausen, K.D. (2015). About the importance of autonomy and digital twins for the future of manufacturing. *IFAC-PapersOnLine*, 48(3):567-572. <https://doi.org/10.1016/j.ifacol.2015.06.141>
- Perrot, A., Pierre, A., Nerella, V.N., Wolfs, R.J. M., Keita, E., Nair, S.A. O., Neithalath, N., Roussel, N., and Mechtcherine, V. (2021). From analytical methods to numerical simulations: A process engineering toolbox for 3D concrete printing. *Cement and Concrete Composites*, 122:104164. <https://doi.org/10.1016/j.cemconcomp.2021.104164>
- Magistri, M. (2024). The cement industry: The challenges of the future. Mapei. <https://www.mapei.com/it/en/realta-mapei/detail/the-cement-industry-the-challenges-of-the-future>
- Cementir Holding. (2024). The cement sector and the challenges of sustainability. Cementir Holding. <https://www.cementirholding.com/en/sustainability/sustainability/cement-sector-and-challenges-of-sustainability>

- Softtek. (2024). Key transformation challenges in the cement industry. Softtek. <https://blog.softtek.com/en/key-transformation-challenges-in-the-cement-industry>
- Chatterjee, A.K. (2021). Digital twin and its variants for advancing digitalization in cement manufacturing. In A. K. Chatterjee (Ed.), *Intelligent and sustainable cement production: Transforming to Industry 4.0 standards* (1st ed., pp. 245–275). CRC Press.
- Wang, Y., Aslani, F., Dyskin, A., and Pasternak, E. (2023). Digital twin applications in 3D concrete printing. *Sustainability*, 15(3):2,124. <https://doi.org/10.3390/su15032124>
- Opoku, D.-G. J., Perera, S., Osei-Kyei, R., & Rashidi, M. (2021). Digital twin application in the construction industry: A literature review. *Journal of Building Engineering*, 40, 102726. <https://doi.org/10.1016/j.jobe.2021.102726>
- Buswell, R. A., da Silva, W. R. L., Bos, F. P., Schipper, H. R., Lowke, D., Hack, N., Kloft, H., Mechtcherine, V., Wangler, T., & Roussel, N. (2020). A process classification framework for defining and describing digital fabrication with concrete. *Cement and Concrete Research*, 134, 106068. <https://doi.org/10.1016/j.cemconres.2020.106068>
- Heidarnazhad, F., & Zhang, Q. (2022). Shotcrete-based 3D concrete printing: State of the art, challenges, and opportunities. *Construction and Building Materials*, 323, 126545. <https://doi.org/10.1016/j.conbuildmat.2022.126545>
- Wang, L., Aslani, F., & Mukherjee, A. (2022). Development of 3D printable self-sensing cementitious composites. *Construction and Building Materials*, 337, 127601. <https://doi.org/10.1016/j.conbuildmat.2022.127601>
- Khan, A., Dahl, M., Falkman, P., & Fabian, M. (2018). Digital twin for legacy systems: Simulation model testing and validation. In *Proceedings of the IEEE International Conference on Automation Science and Engineering (CASE)* (pp. 421–426). IEEE. <https://doi.org/10.1109/COASE.2018.8560338>
- Control Global. (2024). Building information modeling, digital twins create green, smart cement factory. Control Global. <https://www.controlglobal.com/control/ai-ml/article/11290532/building-information-modeling-digital-twins-create-green-smart-cement-factory>
- ZKG International. (2024). Digital transformation of the cement industry. ZKG International. <https://www.zkg.de/en/artikel/digital-transformation-of-the-cement-industry-3968132.html>